

CABLE DE ACERO

GALVANIZADO

- FABRICADO EN ACERO CON
- ACABADO GALVANIZADO
- FUERZA DE TENSIÓN
- DE 1,770 N/MM2
- PARA ARRASTRE Y CARGA
- DE MATERIALES
- TRENZADO REGULAR
- DERECHO (RHRL)
- CMR: CAPACIDAD
- MÁXIMA DE RUPTURA



7X7



Medida	Largo (m)	CMR (T)	Peso neto (100 m/kg)
1/16"	100	0.22	1.11
1/16"	500	0.18	1
1/16"	1,500	0.22	16.65
3/32"	100	0.42	2.39
1/8"	100	0.77	4.26
1/8"	500	0.71	4
1/8"	1,500	0.77	63.9
3/16"	100	1.68	9.18
3/16"	500	1.61	8.9
3/16"	1,500	1.68	137.7
1/4"	100	3.18	15.74
1/4"	500	2.85	15.4
1/4"	1,500	3.18	236.1

Medida	Largo (m)	CM (T)	Capacidad de trabajo (kg)	Peso neto (kg)
3/32"	500	0.37	63	11
1/8"	100	0.91	152	4.3
1/8"	500	0.67	112	19.5
1/8"	1,500	0.91	152	63.9
3/16"	100	1.9	317	9.8
3/16"	500	1.51	252	44
3/16"	1,500	1.9	317	147.6
1/4"	100	3.18	530	16.4
1/4"	500	2.67	446	78
1/4"	1,500	3.18	530	245.9
5/16"	100	4.45	742	25.9
5/16"	500	4.12	687	119
5/16"	1,500	4.45	742	43.5
3/8"	100	6.65	1,092	36.1
3/8"	500	5.93	990	172
3/8"	1,500	6.65	1,092	541.1
7/16"	500	8.15	1,358	235
7/16"	1,500	7.78	1,297	763.4
1/2"	100	9.78		66.44
1/2"	500	10.54	1,757	307.5
1/2"	1,500	9.78	1,630	996.6



CABLE DE ACERO

GALVANIZADO

19X7

