

CABLE DE ACERO CON ALMA DE ACERO

- ACERO ARADO MEJORADO
- FUERZA DE TENSIÓN DE 1,770 N/MM2
- ALMA DE CABLE INDEPENDIENTE (IWRC)
- TRENZADO REGULAR DERECHO (RHRL)
- CMR: CAPACIDAD MÁXIMA DE RUPTURA



6X19

Medida	Largo (m)	CMR (T)	Peso neto (100 m/kg)
1/4"	500	2.7	17.3
5/16"	500	4.2	26.8
5/16"	1000	4.2	26.8
3/8"	500	5.9	38.6
3/8"	1000	5.9	38.6
7/16"	1500	-	-
1/2"	500	10.4	68.4
1/2"	1000	10.4	68.4
5/8"	500	16.2	107.1
3/4"	500	23.2	154.7
7/8"	500	31.4	211.2
1"	500	40.7	274.8

6X26


Medida	Largo (m)	CMR (T)	Peso neto (100 m/kg)
1/4"	500	2.7	17.3
5/16"	500	4.2	26.8
3/8"	500	5.9	38.6
7/16"	1500	-	-
1/2"	500	10.4	68.4
5/8"	500	16.2	107.1
3/4"	500	23.2	154.7
7/8"	500	31.4	211.2
1"	500	40.7	274.8

CABLE DE ACERO CON ALMA DE ACERO

- ACERO ARADO MEJORADO
- FUERZA DE TENSIÓN DE 1,770 N/MM²
- ALMA DE CABLE INDEPENDIENTE (IWRC)
- TRENZADO REGULAR DERECHO (RHRL)
- CMR: CAPACIDAD MÁXIMA DE RUPTURA




6X36



Medida	Largo (m)	CMR (T)	Peso neto (100 m/kg)
1/2"	500	10.4	68.4 kg
7/8"	500	31.4	211.2 kg



19X7



Medida	Largo (m)	CMR (T)	Peso neto (100 m/kg)
3/8"	1,500	5	37.2 kg
1/2"	1,500	8.8	66.9 kg
1/2"	500	-	-
5/8"	500	13.8	105.6 kg
3/4"	500	19.8	151.7 kg