

NUDO PARA CABLE ACERO INOXIDABLE

- FABRICADO EN ACERO INOXIDABLE 304



Tamaño de cable	A (mm)	B (mm)	C (mm)	L (mm)	D (paso)	MIN	INN	MAS
1/8"	14	11	22	20	3/16"	25	0	2000
3/16"	16	13.5	26	24	1/4"	1	0	1000
1/4"	20	17	32	31.5	5/16"	25	0	500
5/16"	22	18.3	35	34	5/16"	25	0	400
3/8"	27	22.5	40	41.8	3/8"	1	0	250
1/2"	35	27	49	53.9	7/16"	1	0	150
3/4"	42	34.5	61	68.7	9/16"	1	0	80

Tamaño de cable	Carga límite de trabajo	MIN	INN	MAS
1/16"	0.05 T	25	0	3000
1/8"	0.13 T	25	0	2000
3/16"	0.31 T	25	0	1000
1/4"	0.49 T	25	0	600
5/16"	0.55 T	20	0	500
3/8"	0.7 T	20	0	300
1/2"	1.14 T	10	0	150
5/8"	2.02 T	1	0	100
3/4"	2.52 T	1	0	80
7/8"	3.49 T	1	0	50
1"	4.61 T	1	0	40
1"	4.61 T	1	0	40



NUDO PARA CABLE MALEABLE

- FABRICADO EN HIERRO MALEABLE
- RESISTENTE A LA CORROSIÓN
- ACABADO GALVANIZADO

NUDO FORJADO PARA CABLE

NUDO GALVANIZADO EN SU TOTALIDAD PARA
RESISTIR LA OXIDACIÓN Y CORROSIÓN



Tamaño de	A (pulg)	B (pulg)	C (pulg)	D (pulg)	E (pulg)	F (pulg)	G (pulg)	H (pulg)	Peso por	MIN	INN	MAS
3/16"	0.25	0.97	0.56	0.59	0.5	0.44	0.94	1.18	10	1	0	300
1/4"	0.31	1.03	0.5	0.75	0.66	0.56	1.19	1.43	19	25	0	300
5/16"	0.38	1.38	0.75	0.88	0.73	0.69	1.31	1.66	28	1	0	200
3/8"	0.44	1.5	0.75	0.91	0.91	0.75	1.63	1.94	48	25	0	120
1/2"	0.5	1.88	1	1.19	1.13	0.88	1.91	2.28	80	10	0	80
5/8"	0.56	2.25	1.25	1.31	1.34	0.94	2.06	2.5	110	1	0	50
3/4"	0.62	2.5	1.44	1.5	1.39	1.06	2.25	2.84	142	1	0	40
7/8"	0.75	3.12	1.62	1.75	1.58	1.25	2.44	3.16	212	1	0	25
1"	0.75	3.5	1.81	1.88	1.77	1.25	2.63	3.47	252	1	0	20
1-1/8"	0.75	3.88	2	2	1.91	1.25	2.81	3.59	283	1	0	20
1-1/4"	0.88	4.44	2.22	2.34	2.17	1.44	3.13	4.13	438	1	0	10
1-3/8"	0.88	4.44	2.22	2.34	2.31	1.44	3.13	4.19	442	1	0	10
1-1/2"	0.88	4.94	2.38	2.59	2.51	1.44	3.41	4.44	544	1	0	10
1-3/4"	1.13	5.75	2.75	3.06	2.92	1.81	3.81	5.24	934	1	0	6
2"	1.25	6.44	3	3.38	3.03	2	4.44	5.88	1300	1	0	4