

# GRILLETE

## PARA CABLE

PERNO CON ROSCA, FORJADOS , TEMPLADOS Y REVENIDOS, CON PERNOS DE ALEACIÓN PARA UTILIZAR EN APLICACIONES DE FIJACIÓN, REMOLQUE, SUSPENSIÓN O APLICACIONES DE IZAJE



| Medida | Carga<br>límite de<br>trabajo | C    | E    | A    | B    | P    | F    | MIN | INN | MAS |
|--------|-------------------------------|------|------|------|------|------|------|-----|-----|-----|
| 1/4"   | 0.5 T                         | 1.13 | 0.78 | 0.47 | 0.31 | 0.25 | 0.61 | 25  | 0   | 500 |
| 5/16"  | 0.75 T                        | 1.22 | 0.84 | 0.53 | 0.38 | 0.31 | 0.75 | 25  | 0   | 400 |
| 3/8"   | 1 T                           | 1.44 | 1.03 | 0.66 | 0.44 | 0.38 | 0.91 | 25  | 0   | 200 |
| 1/2"   | 2 T                           | 1.88 | 1.31 | 0.81 | 0.63 | 0.5  | 1.19 | 5   | 0   | 100 |
| 5/8"   | 3.25 T                        | 2.38 | 1.69 | 1.06 | 0.75 | 0.63 | 1.5  | 5   | 0   | 40  |
| 3/4"   | 4.75 T                        | 2.81 | 2    | 1.25 | 0.88 | 0.75 | 1.81 | 5   | 0   | 20  |
| 7/8"   | 6.5 T                         | 3.19 | 2.27 | 1.44 | 1    | -    | 2.38 | 1   | 0   | 15  |
| 1"     | 8.5 T                         | 3.75 | 2.69 | 1.69 | 1.13 | -    | 2.38 | 1   | 0   | 10  |
| 1-1/8" | 9.5 T                         | 4.25 | 2.91 | 1.81 | 1.25 | 1.16 | 2.69 | 1   | 0   | 6   |
| 1-1/4" | 12 T                          | 4.69 | 3.25 | 2.03 | 1.38 | 1.29 | 3    | 1   | 0   | 5   |
| 1-3/8" | 13.5 T                        | 5.25 | 3.63 | 2.25 | 1.5  | 1.42 | 3.31 | 1   | 0   | 4   |
| 1-1/2" | 17 T                          | 5.75 | 3.88 | 2.38 | 1.63 | 1.54 | 3.63 | 1   | 0   | 3   |
| 1-3/4" | 25 T                          | 7    | 5    | 2.88 | 2    | 1.84 | 4.19 | 1   | 0   | 2   |